

# PT355F

TRUCK MOUNTED TELESCOPIC PLATFORMS

## STANDARD FEATURES

### Performance

- Fly Boom
- Electronic Operation Diagram Limiter
- Electronic Card Controlled Operation
- Proportional Joystick Controller
- Aluminium Basket
- Automatic Basket Leveling
- Lighting on Basket
- Engine Start/Stop System (Vehicle dependent)
- Operator Cabin
- Basket and Turret Control Panels
- Rotating Beacon on Turret
- Buzzer
- All-terrain Outrigger Swivels
- Non-slip Body
- Toolbox (2 pieces)

### Safety

- TS-EN 280 + A1 / CE Conformity
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding Valves and Interlocking Valves against hose blasts
- High Pressure Relief Valve
- Tilt Sensor
- Emergency Descend DC Powerpack



## OPTIONAL FEATURES

- Automatic One-button Platform Leveling
- Fly Boom Rotation (180° Horizontal)
- 70000V Insulated Fiberglass Basket
- Basket Rotation
- Steel Basket
- Basket Load Cell
- Base-Basket Radio Communication
- Extra Basket Capacity
- 110V/220V/380V Socket in Basket
- Toolbox in Basket
- Anemometer on Basket
- Continuous Turret Rotation
- Tilt Sensor
- Digital LED Screen on Control Panel
- External AC Powerpack
- Wireless Remote Joystick Controller
- Emergency Descend DC Powerpack
- Non-slip Aluminium Body
- Additional Toolboxes (+2)
- Additional Lighting
- Custom Paint Color

### TECHNICAL DATA

**PT  
355F**

Operating Height	35 m
Platform Height	33 m
Lateral Outreach	20 m
Turret Rotation	270°
Basket Capacity (kg)	250 kg
Basket Dimensions	850 x 1500 x 1150 mm
Stowed Height	3250 mm
Stowed Length	9150 mm
Stowed Width	2500 mm
Width Outriggers Extended	5400 mm
Control System	Electronic Proportional Joystick
Weight	GVW 18 t

