

PTCR163

TRAILER MOUNTED TELESCOPIC PLATFORMS

STANDARD FEATURES

Performance

- 70000V Insulated Fiberglass Basket
- Automatic Basket Leveling
- Lighting on Basket
- Engine Start/Stop System (Vehicle dependent)
- Electronic Card Controlled Operation
- Proportional Joystick Controller
- Buzzer
- Basket and Turret Control Panels
- Rotating Beacon on Turret
- Manual Outriggers
- All-terrain Outrigger Swivels
- Height Adjustable Front Wheel

Safety

- TS-EN 280 + A1 / CE Conformity
- Simultaneous Braking System with Stop Lights
- Hand Brake
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding Valves and Interlocking Valves against hose blasts
- High Pressure Relief Valve
- Emergency Descend Hand Pump

OPTIONAL FEATURES

- Fly Boom*
- Fly Boom Rotation (180° Horizontal)
- External Drive System
- Hydraulic Outriggers
- Automatic One-button Platform Leveling
- Diesel Engine
- 220V AC Motor
- 24V DC Motor (245Ah Battery)
- Tilt Sensor
- Continuous Turret Rotation
- Basket Load Cell
- Basket Rotation
- 110V/220V/380V Socket in Basket
- Aluminium Basket
- Extra Basket Capacity
- Toolbox in Basket
- Emergency Descend DC Powerpack
- Custom Paint Color
- Additional Lighting
- Hydro mechanical Control System
- Wireless Remote Joystick Controller



Technical Data		PTCR 163
Operating Height		16 m
Platform Height		14 m
Lateral Outreach		10 m
Turret Rotation		350°
Basket Capacity (kg)		200 kg
Basket Dimensions		750x1000x1100 mm
Ⓒ Stowed Height		2850 mm
Ⓐ Stowed Length		6600 mm
Ⓑ Stowed Width		2200 mm
Width Outriggers Extended		4000 mm
Control System		Electronic Proportional Joystick
Weight		2500 kg
Power		220V / 380V AC

