

PT142

TRUCK MOUNTED TELESCOPIC PLATFORMS

STANDARD FEATURES

Performance

- 70000V Insulated Fiberglass Basket
- Automatic Basket Leveling
- Lighting on Basket
- Engine Start/Stop System (Vehicle dependent)
- Electronic Card Controlled Operation
- Proportional Joystick Controller
- Buzzer
- Basket and Turret Control Panels
- Rotating beacon on Turret
- All-terrain Outrigger Swivels
- Non-slip Body
- Toolbox (2 pieces)

Safety

- TS-EN 280 + A1 / CE Conformity
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding Valves and Interlocking Valves against Hose Blasts
- High Pressure Relief Valve
- Emergency Descend Hand Pump

OPTIONAL FEATURES

- Simultaneous Commands Execution (Full proportional)
- Automatic One-button Platform Leveling
- Fly Boom*
- Fly Boom Rotation (180° Horizontal)
- Tilt Sensor
- Basket Load Cell
- Extra Basket Capacity
- Basket Rotation
- Anemometer on Basket
- 110V/220V/380V Socket in Basket
- Aluminium Basket
- Steel Basket
- Toolbox in Basket
- Base-Basket Radio Communication
- Continuous Turret Rotation
- Operator Seat
- Operator Cabin
- Hydro mechanical Control System
- Wireless Remote Joystick Controller
- Emergency Descend DC Powerpack
- External AC Powerpack
- Special Paint Color
- Additional Lighting
- Non-slip Aluminium Body
- Additional Toolboxes (+2)



TECHNICAL DATA		PT 142
Operating Height		14 m
Platform Height		12 m
Lateral Outreach		8 m
Turret Rotation		270°
Basket Capacity (kg)		200 kg
Basket Dimensions		750 x1000x1100 mm
(C) Stowed Height		3160 mm
(A) Stowed Length		5160 mm
(B) Stowed Width		2120 mm
Width Outriggers Extended		2680 mm
Control System		Electronic Proportional Joystick
Weight		1900 kg

