

# PT325F

TRUCK MOUNTED TELESCOPIC PLATFORMS

## STANDARD FEATURES

### Performance

- Fly Boom
- Electronic Operation Diagram Limiter
- Electronic Card Controlled Operation
- Proportional Joystick Controller
- Aluminium Basket
- Automatic Basket Leveling
- Lighting on Basket
- Engine Start/Stop System (Vehicle dependent)
- Operator Cabin
- Basket and Turret Control Panels
- Rotating Beacon on Turret
- Buzzer
- All-terrain Outrigger Swivels
- Non-slip Body
- Toolbox (2 pieces)

### Safety

- TS-EN 280 + A1 / CE Conformity
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding Valves and Interlocking Valves against hose blasts
- High Pressure Relief Valve
- Tilt Sensor
- Emergency Descend DC Powerpack

## OPTIONAL FEATURES

- Automatic One-button Platform Leveling
- Fly Boom Rotation (180° Horizontal)
- 70000V Insulated Fiberglass Basket
- Basket Rotation
- Steel Basket
- Basket Load Cell
- Base-Basket Radio Communication
- Extra Basket Capacity
- 110V/220V/380V Socket in Basket
- Toolbox in Basket
- Anemometer on Basket
- Continuous Turret Rotation
- Tilt Sensor
- Digital LED Screen on Control Panel
- External AC Powerpack
- Wireless Remote Joystick Controller
- Emergency Descend DC Powerpack
- Nonslip Aluminium Body
- Additional Toolboxes (+2)
- Additional Lighting
- Custom Paint Color



### TECHNICAL DATA

### PT 325F

Operating Height	32 m
Platform Height	30 m
Lateral Outreach	20 m
Turret Rotation	270°
Basket Capacity (kg)	250 kg
Basket Dimensions	850x1500x1150 mm
Stowed Height	3250 mm
Stowed Length	8450 mm
Stowed Width	2500 mm
Width Outriggers Extended	5400 mm
Control System	Electronic Proportional Joystick
Weight	GVW 16t

Ⓒ

Ⓐ

Ⓑ

