

PT162

TRUCK MOUNTED TELESCOPIC PLATFORMS

STANDARD FEATURES

Performance

- 70000V Insulated Fiberglass Basket
- Automatic Basket Leveling
- Lighting on Basket
- Engine Start/Stop System (Vehicle dependent)
- Electronic Card Controlled Operation
- Proportional Joystick Controller
- Buzzer
- Basket and Turret Control Panels
- Rotating beacon on Turret
- All-terrain Outrigger Swivels
- Non-slip Body
- Toolbox (2 pieces)

Safety

- TS-EN 280 + A1 / CE Conformity
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding Valves and Interlocking Valves against Hose Blasts
- High Pressure Relief Valve
- Emergency Descend Hand Pump

OPTIONAL FEATURES

- Simultaneous Commands Execution (Full proportional)
- Automatic One-button Platform Leveling
- Fly Boom*
- Fly Boom Rotation (180° Horizontal)
- Tilt Sensor
- Basket Load Cell
- Extra Basket Capacity
- Basket Rotation
- Anemometer on Basket
- 110V/220V/380V Socket in Basket
- Aluminium Basket
- Steel Basket
- Toolbox in Basket
- Base-Basket Radio Communication
- Continuous Turret Rotation
- Operator Seat
- Operator Cabin
- Hydro mechanical Control System
- Wireless Remote Joystick Controller
- Emergency Descend DC Powerpack
- External AC Powerpack
- Special Paint Color
- Additional Lighting
- Nonslip Aluminium Body
- Additional Toolboxes (+2)



TECHNICAL DATA		PT 162
Operating Height		16 m
Platform Height		14 m
Lateral Outreach		9 m
Turret Rotation		270°
Basket Capacity (kg)		200 kg
Basket Dimensions		750 x 1000 x 1100 mm
Ⓒ Stowed Height		3140 mm
Ⓐ Stowed Length		6215 mm
Ⓑ Stowed Width		2185 mm
Width Outriggers Extended		2680 mm
Control System		Electronic Proportional Joystick
Weight		2400 kg

