

PTI426E

FIRE FIGHTING PLATFORMS

STANDART ÖZELLİKLER

Performans

- Telescopic Articulated Boom
- Rescue Ladder
- 3.000 l/min High Pressure Water Pump
- Min. 40.m Hose Reel
- Min 20m Hose Reel On Basket
- 2.500 l/min Water Monitor
- One Button Easy Leveling
- Simultaneous Commands Executable Joystick Controller
- Flashing Beacon with Paging
- Proportional Joystick Controller
- -10 degrees Operating Angle
- Electronic Operating Diagram Limiter
- CANBUS Electronic Systems Control
- Digital Screen
- Operator Seat on Base
- Compartments with Roll-up Doors
- Compartment Lighting
- Anemometer
- Stretcher Extension on Basket
- Basket Load Sensor
- Basket Base Communication System
- Lighting on Basket
- Ultrasonic Proximity Sensors

Güvenlik

- TS-EN 280 + A1 / CE Conformity
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding and Interlocking Valves against Hose Blasts
- High Pressure Relief Valve
- Emergency Descend DC Powerpack

OPSİYONEL ÖZELLİKLER

- 110V / 220V / 380V Socket in Basket
- Toolbox on Basket
- Remote Controlled Water Monitor
- Operator Cabin
- Additional Lighting



Technical Data

PTI
426E

Vehicle Segment	6x4 (26 t)
Operating Height	42 m
Platform Height	40 m
Lateral Outreach	20 m
Basket Capacity	800x2000x1100 mm
Basket Dimensions	400 kg
Turret Rotation	350°

