

# PTCE164

TRUCK MOUNTED DOUBLE ARTICULATED TELESCOPIC PLATFORMS

## STANDARD FEATURES

### Performance

- 70000V Insulated Fiberglass Basket
- Automatic Basket Leveling
- Lighting on Basket
- Engine Start/Stop System (Vehicle dependent)
- Electronic Card Controlled Operation
- Proportional Joystick Controller
- Buzzer
- Basket and Turret Control Panels
- Rotating beacon on Turret
- All-terrain Outrigger Swivels
- Non-slip Body
- Toolbox (2 pieces)

### Safety

- TS-EN 280 + A1 / CE Conformity
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding Valves and Interlocking Valves against Hose Blasts
- High Pressure Relief Valve
- Emergency Descend Hand Pump



## OPTIONAL FEATURES

- Simultaneous Commands Execution (Full proportional)
- Automatic One-button Platform Leveling
- Fly Boom\*
- Fly Boom Rotation (180° Horizontal)
- Tilt Sensor
- Basket Load Cell
- Extra Basket Capacity
- Basket Rotation
- Anemometer on Basket
- 110V/220V/380V Socket in Basket
- Aluminium Basket
- Steel Basket
- Toolbox in Basket
- Base-Basket Radio Communication
- Continuous Turret Rotation
- Operator Seat
- Operator Cabin
- Hydro mechanical Control System
- Wireless Remote Joystick Controller
- Emergency Descend DC Powerpack
- External AC Powerpack
- Special Paint Color
- Additional Lighting
- Non-slip Aluminium Body
- Additional Toolboxes (+2)

### TECHNICAL DATA

**PTCE  
164**

Operating Height	16 m
Platform Height	14 m
Lateral Outreach	5,5 m
Turret Rotation	270°
Basket Capacity (kg)	200 kg
Basket Dimensions	750x1000x1100 mm
<b>(C)</b> Stowed Height	2800 mm
<b>(A)</b> Stowed Length	4900 mm
<b>(B)</b> Stowed Width	2100 mm
Width Outriggers Extended	2580 mm
Control System	Joystick
Weight	2000 kg

