

PT305

TRUCK MOUNTED TELESCOPIC PLATFORMS

STANDARD FEATURES

Performance

- Aluminium Basket
- Automatic Basket Leveling
- Lighting on Basket
- Engine Start/Stop System (Vehicle dependent)
- Electronic Card Controlled Operation
- Proportional Joystick Controller
- Buzzer
- Basket and Turret Control Panels
- Rotating beacon on Turret
- All-terrain Outrigger Swivels
- Non-slip Body
- Toolbox (2 pieces)

Safety

- TS-EN 280 + A1 / CE Conformity
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding Valves and Interlocking Valves against hose blasts
- High Pressure Relief Valve
- Emergency Descend Hand Pump
- Electronic Operation Diagram Limiter

OPTIONAL FEATURES

- Fly Boom*
- Fly Boom Rotation (180° Horizontal)
- 70000V Insulated Fiberglass Basket
- Basket Rotation
- Steel Basket
- Basket Load Cell
- 110V/220V/380V Socket in Basket
- Hanging Basket (Foldable)
- Base-Basket Radio Communication
- Extra Basket Capacity
- Anemometer on Basket
- Toolbox in Basket
- Continuous Turret Rotation
- Operator Seat
- Operator Cabin
- Wireless Remote Joystick Controller
- Hydro mechanical Control System
- External AC Powerpack
- Emergency Descend DC Powerpack
- Tilt Sensor
- Digital LED Screen on Control Panel
- Nonslip Aluminium Body
- Additional Toolboxes (+2)
- Additional Lighting
- Special Paint Color



TECHNICAL DATA	PT 305
Operating Height	30 m
Platform Height	28 m
Lateral Outreach	18 m
Turret Rotation	270°
Basket Capacity (kg)	200 kg
Basket Dimensions	750 x 1400 x 1100 mm
(C) Stowed Height	3100 mm
(A) Stowed Length	7050 mm
(B) Stowed Width	2220 mm
Width Outriggers Extended	5000 mm
Control System	Electronic Proportional Joystick
Weight	6000 kg

