

PTP123F

SPIDER PLATFORMS

STANDARD FEATURES

Performance

- Easy Onboard Calibration®
- 350° Turret Rotation
- Speed / Torque Drive Selection
- Hydromotors with brake
- Fly Boom
- 25% Gradability
- Cable Remote Joystick Controller
- 20% Gradability
- Digital Control Panel
- Aluminium Basket
- Non marking Grey Tires
- Orange - White Paint
- Hour Meter
- Lighting on Basket
- Rotating Beacon on Turret
- Horn

Safety

- TS-EN 280 + A1 / CE Conformity
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding and Interlocking Valves against Hose Blasts
- High Pressure Relief Valve
- Emergency Descend Hand Pump
- Descend Buzzer



OPTIONAL FEATURES

- Fly Rotation (180° Horizontal)
- Basket Rotation
- 70000V Insulated Fiberglass Basket
- Steel Basket
- Basket Load Cell
- 110V / 220V / 380V Socket in Basket
- Basket Toolbox
- Air Outlet on Basket
- Anemometer on Basket
- Extra Basket Capacity
- Wireless Remote Controller
- Diesel Engine
- Continuous Turret Rotation
- Custom Paint Color
- Additional Lighting

TECHNICAL DATA		PTP 123F
Operating Height		12 m
Platform Height		10 m
Lateral Outreach		6 m
Turret Rotation		350°
Basket Capacity (kg)		200 kg
Basket Dimensions		800x1300x1100 mm
(A) Stowed Height		1950 mm
(B) Stowed Length		4750 mm
(C) Stowed Width		1100 mm
Control System		Electronic Proportional Joystick
Weight		2650 kg
Batteries		480 Ah/24V DC (12V x2)
Battery Charger		70Ah
Drive System		Track Driven

