

PT375E

TRUCK MOUNTED TELESCOPIC PLATFORMS

STANDARD FEATURES

Performance

- Simultaneous Commands Execution (Full proportional)
- Electronic Card Controlled Operation
- Proportional Joystick Controller
- Aluminium Basket
- Automatic Basket Leveling
- Lighting on Basket
- Basket Rotation
- Ultrasonic Proximity Sensors
- Engine Start/Stop System (Vehicle dependent)
- Operator Cabin
- Basket and Turret Control Panels
- Rotating Beacon on Turret
- Buzzer
- All-terrain Outrigger Swivels
- Nonslip Aluminium Body
- Toolbox (2 pieces)
- Jib Boom (180° ±5 Degrees Vertical)

Safety

- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding Valves and Interlocking Valves against hose blasts
- High Pressure Relief Valve
- Tilt Sensor
- Emergency Descend DC Powerpack



OPTIONAL FEATURES

- Basket Load Cell
- Base-Basket Radio Communication
- Extra Basket Capacity
- Anemometer on Basket
- 110V/220V/380V Socket in Basket
- Toolbox in Basket
- Digital LED Screen on Control Panel
- Wireless Remote Joystick Controller
- Continuous Turret Rotation
- External AC Powerpack
- Additional Toolboxes (+2)
- Additional Lighting
- Special Paint Color

TECHNICAL DATA

**PT
375E**

Operating Height	37 m
Platform Height	35 m
Lateral Outreach	22 m
Turret Rotation	350°
Basket Capacity (kg)	400 kg
Basket Dimensions	1000x2250x1150 mm
Stowed Height	3350 mm
Stowed Length	9200 mm
Stowed Width	2500 mm
Width Outriggers Extended	5600 mm
Control System	Electronic Proportional Joystick
Weight	GVW 18 t

©
A
B

