

PMY84M

SCISSOR LIFT

STANDARD FEATURES

Performance

- Easy Onboard Calibration®
- Drive speed proportional to height
- Drive at height
- Speed / Torque Drive Selection
- Front Wheel Drive
- Drive speed proportional to height
- 20% Gradability
- Drive Traction Control System
- Proportional Joystick Controller
- Digital Control Panel
- Customizable Descend Speed
- Foldable Guardrails
- Rotating Beacon on Base
- Non marking Grey Tires
- Horn
- Self Lubricating Bearings
- Hour Meter
- Orange - White Paint
- Forklift Holes

Safety

- TS-EN 280 + A1 / CE Conformity
- Pothole Protection Outriggers
- Emergency Stop Buttons on Control Panels
- Tilt Sensor
- High Pressure Relief Valve
- Brake Release Valve
- Descend Buzzer
- Pressure Holding and Interlocking Valves against Hose Blasts
- Emergency Descend Hand Valve

OPTIONAL FEATURES

- Diesel Engine
- Wireless Remote Controller
- Hydraulic Basket Extension
- Basket Air Outlet
- 110V / 220V / 380V Socket in Basket
- Anemometer on Basket
- Basket Toolbox
- Heavy Duty Solid Rubber Tires
- Additional Lighting
- Custom Paint Color



TECHNICAL DATA	PMY 84M
Operating Height	7,8 m
Platform Height	5,8 m
Basket Capacity (kg)	230 kg
Basket Dimensions	1100 x 1670 x 740 mm
Full Height	2150 mm
Height Guardrails Folded	1850 mm
Length	1880 mm
Width	760 mm
Basket Extension	0,9 m
Basket Extension Capacity	120 kg / 1 Person
Control System	Electronic Proportional Joystick
Weight	1450 kg
Batteries	210Ah/24V DC (6Vx4)
Battery Charger	24V 25Amp/h
Drive System	Hydromotor
Drive Speed (Min/Max)	0,8km/h-3,5km/h

- Ⓒ
- Ⓐ
- Ⓑ
- Ⓕ
- Ⓓ

