

PTCR123

TRAILER MOUNTED TELESCOPIC PLATFORMS

STANDARD FEATURES

Performance

- 70000V Insulated Fiberglass Basket
- Automatic Basket Leveling
- Lighting on Basket
- Engine Start/Stop System (Vehicle dependent)
- Electronic Card Controlled Operation
- Proportional Joystick Controller
- Buzzer
- Basket and Turret Control Panels
- Rotating Beacon on Turret
- Manual Outriggers
- All-terrain Outrigger Swivels
- Height Adjustable Front Wheel

Safety

- TS-EN 280 + A1 / CE Conformity
- Simultaneous Braking System with Stop Lights
- Hand Brake
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding Valves and Interlocking Valves against hose blasts
- High Pressure Relief Valve
- Emergency Descend Hand Pump

OPTIONAL FEATURES

- Fly Boom*
- Fly Boom Rotation (180° Horizontal)
- External Drive System
- Hydraulic Outriggers
- Automatic One-button Platform Leveling
- Diesel Engine
- 220V AC Motor
- 24V DC Motor (245Ah Battery)
- Tilt Sensor
- Continuous Turret Rotation
- Basket Load Cell
- Basket Rotation
- 110V/220V/380V Socket in Basket
- Aluminium Basket
- Extra Basket Capacity
- Toolbox in Basket
- Emergency Descend DC Powerpack
- Custom Paint Color
- Additional Lighting
- Hydro mechanical Control System
- Wireless Remote Joystick Controller



Technical Data	PTCR 123
Operating Height	12 m
Platform Height	10 m
Lateral Outreach	6,5 m
Turret Rotation	350°
Basket Capacity (kg)	200 kg
Basket Dimensions	750x1000x1100 mm
(C) Stowed Height	2400 mm
(A) Stowed Length	5500 mm
(B) Stowed Width	2000 mm
Width Outriggers Extended	3500 mm
Control System	Electronic Proportional Joystick
Weight	+/- 1750 kg
Power	220V / 380V AC

