

# PTP203F

SPIDER PLATFORMS

## STANDARD FEATURES

### Performance

- Easy Onboard Calibration®
- 350° Turret Rotation
- Speed / Torque Drive Selection
- Hydromotors with brake
- Fly Boom
- 25% Gradability
- Cable Remote Joystick Controller
- 20% Gradability
- Digital Control Panel
- Aluminium Basket
- Non marking Grey Tires
- Orange - White Paint
- Hour Meter
- Lighting on Basket
- Rotating Beacon on Turret
- Horn

### Safety

- TS-EN 280 + A1 / CE Conformity
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding and Interlocking Valves against Hose Blasts
- High Pressure Relief Valve
- Emergency Descend Hand Pump
- Descend Buzzer



## OPTIONAL FEATURES

- Fly Rotation (180° Horizontal)
- Basket Rotation
- 70000V Insulated Fiberglass Basket
- Steel Basket
- Basket Load Cell
- 110V / 220V / 380V Socket in Basket
- Basket Toolbox
- Air Outlet on Basket
- Anemometer on Basket
- Extra Basket Capacity
- Wireless Remote Controller
- Diesel Engine
- Continuous Turret Rotation
- Custom Paint Color
- Additional Lighting

### TECHNICAL DATA

### PTP 203F

Operating Height	20 m
Platform Height	18 m
Lateral Outreach	10 m
Turret Rotation	350°
Basket Capacity (kg)	200 kg
Basket Dimensions	800x1300x1100 mm
<b>(A)</b> Stowed Height	2000 mm
<b>(B)</b> Stowed Length	7325 mm
<b>(C)</b> Stowed Width	1250 mm
Control System	Electronic Proportional Joystick
Weight	4000 kg
Batteries	480 Ah/24V DC (12V x2)
Battery Charger	70Ah
Drive System	Track Driven

