

# PT426E

TRUCK MOUNTED TELESCOPIC PLATFORMS



## STANDARD FEATURES

### Performance

- Simultaneous Commands Execution (Full proportional)
- Electronic Card Controlled Operation
- Proportional Joystick Controller
- Aluminium Basket
- Automatic Basket Leveling
- Lighting on Basket
- Basket Rotation
- Anemometer on Basket
- Base-Basket Radio Communication
- Digital LED Screen on Control Panel
- Ultrasonic Proximity Sensors
- Engine Start/Stop System (Vehicle dependent)
- Operator Cabin
- Basket and Turret Control Panels
- Rotating Beacon on Turret
- Buzzer
- All-terrain Outrigger Swivels
- Nonslip Aluminium Body
- Toolbox (2 pieces)
- Jib Boom (180° ±5 Degrees Vertical)

### Safety

- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding Valves and Interlocking Valves against hose blasts
- High Pressure Relief Valve
- Tilt Sensor
- Emergency Descend DC Powerpack

## OPTIONAL FEATURES

- Basket Load Cell
- Base-Basket Radio Communication
- Extra Basket Capacity
- Anemometer on Basket
- 110V/220V/380V Socket in Basket
- Toolbox in Basket
- Digital LED Screen on Control Panel
- Wireless Remote Joystick Controller
- Continuous Turret Rotation
- External AC Powerpack
- Additional Toolboxes (+2)
- Additional Lighting
- Special Paint Color

TECHNICAL DATA		PT 426E
Operating Height		42 m
Platform Height		40 m
Lateral Outreach		25 m
Turret Rotation		350°
Basket Capacity (kg)		400 kg
Basket Dimensions		1000x2400x1150 mm
Ⓒ Stowed Height		3450 mm
Ⓐ Stowed Length		9750 mm
Ⓑ Stowed Width		2500 mm
Width Outriggers Extended		5750 mm
Control System		Electronic Proportional Joystick
Weight		GVW 26 t

