

PTE123

TRUCK MOUNTED ARTICULATED TELESCOPIC PLATFORMS

STANDARD FEATURES

Performance

- 70000V Insulated Fiberglass Basket
- Automatic Basket Leveling
- Lighting on Basket
- Engine Start/Stop System (Vehicle dependent)
- Electronic Card Controlled Operation
- Proportional Joystick Controller
- Buzzer
- Basket and Turret Control Panels
- Rotating beacon on Turret
- All-terrain Outrigger Swivels
- Non-slip Body
- Toolbox (2 pieces)

Safety

- TS-EN 280 + A1 / CE Conformity
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding Valves and Interlocking Valves against Hose Blasts
- High Pressure Relief Valve
- Emergency Descend Hand Pump

OPTIONAL FEATURES

- Tilt Sensor
- Basket Rotation
- Basket Load Cell
- Extra Basket Capacity
- Aluminium Basket
- Steel Basket
- Toolbox in Basket
- Anemometer on Basket
- 110V/220V/380V Socket in Basket
- Wireless Remote Joystick Controller
- Hydro mechanical Control System
- Continuous Turret Rotation
- Base-Basket Radio Communication
- Emergency Descend DC Powerpack
- External AC Powerpack
- Special Paint Color
- Additional Lighting



TECHNICAL DATA		PTE 123
Operating Height		12 m
Platform Height		10 m
Lateral Outreach		5 m
Turret Rotation		200°
Basket Capacity (kg)		160 kg
Basket Dimensions		750x1000x1100 mm
(A) Stowed Height		2250 mm
(C) Stowed Length		4350 mm
(B) Stowed Width		2000 mm
Width Outriggers Extended	Electronic Proportional Joystick	
Weight		1000 kg

