

PTP254F

SPIDER PLATFORMS

STANDARD FEATURES

Performance

- Easy Onboard Calibration®
- 350° Turret Rotation
- Speed / Torque Drive Selection
- Hydromotors with brake
- Fly Boom
- 25% Gradability
- Cable Remote Joystick Controller
- 20% Gradability
- Digital Control Panel
- Aluminium Basket
- Non marking Grey Tires
- Orange - White Paint
- Hour Meter
- Lighting on Basket
- Rotating Beacon on Turret
- Horn

Safety

- TS-EN 280 + A1 / CE Conformity
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding and Interlocking Valves against Hose Blasts
- High Pressure Relief Valve
- Emergency Descend Hand Pump
- Descend Buzzer



OPTIONAL FEATURES

- Fly Rotation (180° Horizontal)
- Basket Rotation
- 70000V Insulated Fiberglass Basket
- Steel Basket
- Basket Load Cell
- 110V / 220V / 380V Socket in Basket
- Basket Toolbox
- Air Outlet on Basket
- Anemometer on Basket
- Extra Basket Capacity
- Wireless Remote Controller
- Diesel Engine
- Continuous Turret Rotation
- Custom Paint Color
- Additional Lighting

TECHNICAL DATA

PTP 254F

Operating Height	25 m
Platform Height	23 m
Lateral Outreach	12 m
Turret Rotation	350°
Basket Capacity (kg)	200 kg
Basket Dimensions	800x1300x1100 mm
(A) Stowed Height	2000 mm
(B) Stowed Length	8000 mm
(C) Stowed Width	1400 mm
Control System	Electronic Proportional Joystick
Weight	4750 kg
Batteries	Diesel + 220V
Battery Charger	Alternator
Drive System	Track Driven

