

PTI274

FIRE FIGHTING PLATFORMS

STANDARD FEATURES

Performance

- Telescopic Boom
- Rescue Ladder
- 3.000 l Water Tank
- 250 l Foam Tank
- 3.000 l/min High Pressure Water Pump
- Min. 40.m Hose Reel
- Min 20m Hose Reel On Basket
- 2.500 l/min Water Monitor
- Simultaneous Commands Executable Joystick Controller
- Flashing Beacon with Paging
- Proportional Joystick Controller
- -10 degrees Operating Angle
- Electronic Operating Diagram Limiter
- CANBUS Electronic Systems Control
- Operator Seat on Base
- Compartments with Roll-up Doors
- Compartment Lighting
- Lighting on Basket

Safety

- TS-EN 280 + A1 / CE Conformity
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding and Interlocking
- Valves against Hose Blasts
- High Pressure Relief Valve
- Emergency Descend Hand Pump

OPTIONAL FEATURES

- One Button Easy Leveling
- Ultrasonic Proximity Sensors
- 110V / 220V / 380V Socket in Basket
- Toolbox on Basket
- Remote Controlled Water Monitor
- Basket Base Communication System
- Operator Cabin
- Emergency Descend DC Powerpack
- Anemometer
- Additional Lighting
- Digital Screen



Technical Data

PTI
274

Vehicle Segment	4x2 (18 t)
Operating Height	27 m
Platform Height	25 m
Lateral Outreach	20 m
Basket Capacity	800x1400x1100 mm
Basket Dimensions	250 kg
Turret Rotation	350°

