

PMY186

SCISSOR LIFT

STANDARD FEATURES

Performance

- Easy Onboard Calibration®
- Drive speed proportional to height
- Drive at height
- Speed / Torque Drive Selection
- Front Wheel Drive
- Drive speed proportional to height
- 20% Gradability
- Drive Traction Control System
- Proportional Joystick Controller
- Digital Control Panel
- Customizable Descend Speed
- Foldable Guardrails
- Rotating Beacon on Base
- Non marking Grey Tires
- Horn
- Self Lubricating Bearings
- Hour Meter
- Orange – White Paint
- Forklift Holes

Safety

- TS-EN 280 + A1 / CE Conformity
- Emergency Stop Buttons on Control Panels
- Tilt Sensor
- High Pressure Relief Valve
- Brake Release Valve
- Descend Buzzer
- Pressure Holding and Interlocking Valves against Hose Blasts
- Emergency Descend Hand Valve

OPTIONAL FEATURES

- Diesel Engine
- Wireless Remote Controller
- Hydraulic Basket Extension
- Basket Air Outlet
- 110V / 220V / 380V Socket in Basket
- Anemometer on Basket
- Basket Toolbox
- Heavy Duty Solid Rubber Tires
- Additional Lighting
- Custom Paint Color



TECHNICAL DATA		PMY 186
Operating Height		18 m
Platform Height		16 m
Basket Capacity (kg)		400 kg
Basket Dimensions		1600x3320x1100 mm
(C) Full Height		3100 mm
(A) Height Guardrails Folded		2325 mm
(B) Length		3400 mm
(F) Width		1800 mm
(D) Basket Extension		1,5 m
Basket Extension Capacity		120 kg / 1 Person
Control System		Electronic Proportional Joystick
Weight		5250 kg
Batteries		640Ah/24V DC (2Vx12)
Battery Charger		24V 100Amp/h
Drive System		Hydromotor
Drive Speed (Min/Max)		2km/h-3km/h

