

PMY83

SCISSOR LIFT

STANDARD FEATURES

Performance

- Easy Onboard Calibration®
- Drive speed proportional to height
- Drive at height
- Speed / Torque Drive Selection
- Front Wheel Drive
- Drive speed proportional to height
- 20% Gradability
- Drive Traction Control System
- Proportional Joystick Controller
- Digital Control Panel
- Customizable Descend Speed
- Foldable Guardrails
- Rotating Beacon on Base
- Non marking Grey Tires
- Horn
- Self Lubricating Bearings
- Hour Meter
- Orange - White Paint
- Forklift Holes

Safety

- TS-EN 280 + A1 / CE Conformity
- Pothole Protection Outriggers
- Emergency Stop Buttons on Control Panels
- Tilt Sensor
- High Pressure Relief Valve
- Brake Release Valve
- Descend Buzzer
- Pressure Holding and Interlocking Valves against Hose Blasts
- Emergency Descend Hand Valve

OPTIONAL FEATURES

- Diesel Engine
- Wireless Remote Controller
- Hydraulic Basket Extension
- Basket Air Outlet
- 110V / 220V / 380V Socket in Basket
- Anemometer on Basket
- Basket Toolbox
- Heavy Duty Solid Rubber Tires
- Additional Lighting
- Custom Paint Color



TECHNICAL DATA	PMY 83
Operating Height	8 m
Platform Height	6 m
Basket Capacity (kg)	300 kg
Basket Dimensions	1100 x 2275 x 1100 mm
(C) Full Height	2220 mm
(A) Height Guardrails Folded	1490 mm
(B) Length	2510 mm
(F) Width	1150 mm
(D) Basket Extension	0,9 m
Basket Extension Capacity	120 kg / 1 Person
Control System	Electronic Proportional Joystick
Weight	2150 kg
Batteries	245Ah/24V DC (6Vx4)
Battery Charger	24V 40Amp/h
Drive System	Hydromotor
Drive Speed (Min/Max)	2km/h-4km/h

