

PTE133 Tractor

TRUCK MOUNTED ARTICULATED TELESCOPIC PLATFORMS

STANDARD FEATURES

Performance

- 70.000V Insulated Fiberglass Basket
- Automatic Basket Leveling
- Lighting on Basket
- Engine Start/Stop System (Vehicle dependent)
- Electronic Card Controlled Operation
- Proprtional Joystick Controller
- Buzzer
- Basket and Turret Control Panels
- Rotating Beacon on Turret
- Easy Attaching-Dismounting Feature
- All-Terrain Outrigger Swivels
- Non-Slip Body

Safety

- TS-EN 280 + A1 / CE Conformity
- Emergency Bypass® System
- Emergency Stop Buttons on Control Panels
- Pressure Holding Valves and Interlocking Valves against Hose Blasts
- High Pressure Relief Valve
- Emergency Descend Hand Pump

OPTIONAL FEATURES

- Tilt Sensor
- Basket Rotation
- Basket Load Cell
- Extra Basket Capacity
- Aluminium Basket
- Steel Basket
- Additional Lighting
- Toolbox in Basket
- 220V/380V Socket in Basket
- Wireless Remote Joystick Controller
- Hydro Mechanical Control System
- External AC Powerpack
- Emergency Descend DC Powerpack
- Special Paint Color



TECHNICAL DATA

**PTE
133**

Operating Height	13 m
Platform Height	11 m
Lateral Outreach	4,5 m
Turret Rotation	180°
Basket Capacity (kg)	200 kg
Basket Dimensions	750x1000x1100 mm
(A) Stowed Height	2750 mm
(C) Stowed Length	2000 mm
(B) Stowed Width	2400 mm
Width Outriggers Extended	Electronic Proportional Joystick
Weight	1500 kg

